



# 2W Ku-Band Block Up Converter

## KEY FEATURES


- ◆ Smallest package size and weight
- ◆ Feed horn mounting
- ◆ Powered through IF cable
- ◆ Low power consumption (<17W)
- ◆ 14.00-14.50 GHz / 13.75-14.25 GHz / 13.75-14.50 GHz options
- ◆ High power efficiency (2W min @P1dB over temperature)
- ◆ RoHS compliant
- ◆ Three-year warranty

**ABAN2KU / ABAN2KUF**  
**ABAN2KUL / ABAN2KULF**  
**ABAN2KUX / ABAN2KUXF**



This small and light weight 2W L-To Ku-Band Block Up Converter is designed to be mounted on the feed horn. High power efficiency resulting in low current (< 1 amps) consumption allows user to pass DC supply voltage via IF cable. The unit is ideal for network and point to point, data distribution, portable and emergency applications.

## Mechanical Drawing



# 2W Ku-Band Block Up Converter

## TECHNICAL SPECIFICATIONS

<b>RF frequency</b>	<b>ABAN2KU</b> <b>ABAN2KUL</b> <b>ABAN2KUX</b>	14.00 to 14.50 GHz 13.75 to 14.25 GHz 13.75 to 14.50 GHz
<b>Local oscillator</b>	<b>ABAN2KU</b> <b>ABAN2KUL</b> <b>ABAN2KUX</b>	13.05 GHz 12.80 GHz 12.80 GHz
<b>IF frequency</b>		950 to 1,700 MHz
<b>Output power @ P1dB min over temperature</b>		2W (+34 dBm min.)
<b>IF connector</b>		N-type or F-type
<b>Power supply</b>		+15 VDC~+24 VDC via IF cable 17 W max
<b>Output interface</b>		WR-75 Grooved
<b>Gain</b>		60 dB nominal
<b>IMD3</b>		-32 dBc max
<b>L.O. leakage</b>		-50 dBm max
<b>Spurious</b>		-50 dBc max
<b>Gain variation</b>	<b>over 54 MHz</b> <b>over 500 MHz</b>	0.7 dB p_p 2.0 dB p_p 2.2 dB p_p @ fixed frequency
<b>Over operating temperature</b>		
<b>Requirement for external reference</b>		via IF cable
frequency		10 MHz (sine-wave)
input power		-5 to +5 dBm @ input port
<b>Phase noise</b>		-53 dBc/Hz max. @ 10 Hz -63 dBc/Hz max. @ 100 Hz -73 dBc/Hz max. @ 1 KHz -83 dBc/Hz max. @ 10 KHz -93 dBc/Hz max. @ 100 KHz -110 dBc/Hz max @ 1 MHz
<b>Noise figure</b>		20 dB max
<b>Input V.S.W.R.</b>		2 : 1 max
<b>Output V.S.W.R.</b>		2 : 1 max.
<b>Mute</b>		Shut off the BUC in case of L.O. unlocked
<b>Input interface</b>	<b>ABAN2KU</b> <b>ABAN2KUF</b>	50 Ohm (N-type IF in) 75 Ohm (F-type IF in)
<b>Temperature range (ambient)</b>		
operating		-40 deg C to +55 deg C
storage		-40 deg C to +75 deg C
<b>Dimensions &amp; housing</b>		128.7 (L) x 94.8 (W) x 57 (H) mm 5.06" (L) x 3.73" (W) x 2.24" (H)
<b>Weight</b>		0.72 kg (1.58 lbs)