

LS32 2150A LS322150A1FVB000

QUALITY MANAGEMENT SYSTEM
CERTIFIED BY DNV

150 9001:2000

32-Way Active Splitter (950-2150 MHz)

General Description:

The **LS322150A1FVB000** is a commercial quality 32-way splitter that meets strict level and match specifications achieved through the use of Quintech's proprietary microstrip and SMT technology. It operates over the 950-2150 MHz frequency range and permits signal splitting with zero loss, eliminating the need for external distribution amplifiers. The LS322150A1FVB000 provides LNB DC power insertion that can be switched on or off via the front panel mounted slide switch (see LNB Power specification below).

Note: All unused ports must have 75 Ω terminations.

Specifications:

Frequency: 950-2150 MHz

Impedance: 75Ω P1dB: -10 dBm **Insertion Loss:** 0 + 2 dB**Frequency Response:** + 2 dB 18 dB Isolation: 12 dB **Input Return Loss: Output Return Loss:** 12 dB **Noise Figure:** 12 dB

RF Connectors: Type F, 75 Ω

Power Requirements: 18-24 V===, via 2-pin quick connect barrier strip

LNB Power: 18 V=== (800 mA max. available for LNB power

Power Consumption: 12 W, plus customer LNB power load

 Mechanical:
 2 RU (3.5" H x 19" W x 14" D)

 Weight:
 11 lbs. gross (boxed), 6.2 lbs. net

Certifications: CE



