

PROGRAMMABLE SCPC/VSAT MODEM

FEATURES

- ◆ BPSK, QPSK, OQPSK, 8PSK, 16QAM
- ◆ Programmable receive acquisition/tracking range
- ◆ Typical DSP acquisition time of 315 msec at 9.6 kbps QPSK, 71 msec at 64 kbps QPSK.
- ◆ Viterbi and Reed-Solomon FEC standard, TPC optional. BER vs. Eb/No performance within 0.3 dB of theoretical. 10⁻⁷ BER at 6.0 dB Eb/No (2.8 dB with TPC, 3.5 dB with Reed-Solomon codec)
- ◆ DDS transmit and receive frequency setting in 1 Hz increments
- ◆ Programmable Interface type
- ◆ Low power, light weight 1 U case
- ◆ DDS setting of transmit and receive data rates from 1.2Kbps to 20Mbps in 1 bps increments
- ◆ Built-in BER Test Set.
- ◆ Built-in IBS Multiplexer with overhead channel, AUPC and Remote Modem Control
- ◆ 40 dB AGC range with +15 dBm composite input power
- ◆ Fully programmable from either front panel or remote command without jumpers
- ◆ Viterbi FEC codec programmable to rate 1/2, 3/4, 5/6, 7/8 and disabled
- ◆ Built-in 1:1 Redundancy
- ◆ Designed to use internal or external G.703 and Ethernet interfaces
- ◆ 140 MHz IF available on request
- ◆ 8 User stored and recallable configurations. Automatic Recovery of stored configurations

PSM-500S Series



Datum Systems' latest satellite modem implementation represents state of the art enhancements to the popular PSM-4900 series of modems at the industry's lowest price. The PSM-500S, or "M500S" uses Datum Systems' proprietary techniques of direct modulation and demodulation to completely eliminate transmit and receive IF sections and their associated filters. Sophisticated digital signal processing eliminates all on board physical adjustments and provides performance within 0.3 dB of theoretical. Direct Digital Synthesis (DDS) of the transmit, receive and data rate synthesizers allow settings to 1 Hz and 1 bps respectively. The PSM-500S, 70 MHz IF version is ideal for hub stations while the companion L-Band M500L is optimized for low cost, high performance VSATs and small stations. The PSM-500S series adds 8PSK, 16QAM, Reed-Solomon and a built-in multiplexer to the PSM-4900 series.

The PSM-500S series is unmatched by any other modem in its class for fast acquisition, BER performance and power/bandwidth optimization. It uses dedicated DSP for extremely fast acquisition over a programmable range.

The PSM-500S is available in 3 upgradable versions, the PSM-505S, PSM-511S and PSM-523S offering the latest modulation, coding and FEC technology plus data rates to precisely meet your needs. The transmit and receive can independently use BPSK, QPSK, OQPSK, 8PSK and 16QAM modulation at any data rate or configuration settings. Reed-Solomon, IBS multiplexer, AUPC and remote modem control channels are built-in. Sophisticated TPC and other FEC options are available.

The full front panel provides a backlit LCD display, full keypad and LED indicators for monitor and control of all modem parameters.

PSM-500 Series Feature Matrix

Feature	PSM-4900	PSM-505S	PSM-511S	PSM-523S
MODULATION				
BPSK	x	x	x	x
QPSK	x	x	x	x
OQPSK	N/A	x	x	x
8PSK/TCM	N/A	Upg	x	x
16QAM/APSK	N/A	Upg	Upg	x
Max Data Rate				
BPSK	2.46 Mbps	2.5 Mbps	5 Mbps	7.38 Mbps
QPSK/OQPSK	4.92 Mbps	5 Mbps	10 Mbps	14.76 Mbps
8PSK/TCM	N/A	N/A	10 Mbps	20 Mbps
16QAM/APSK	N/A	N/A	N/A	20 Mbps
FEC Modes				
Viterbi	Option	x	x	x
Reed-Solomon	Option	x	x	x
TPC - 4K	Option	Option	Option	Option
TPC - 16K	N/A	Option	Option	Option
FLDPC	N/A	Option	Option	Option
IBS Mux/AUPC	Option	x	x	x

SPECIFICATIONS

Operating Modes, all programmable:	Receive and Transmit Continuous (SCPC), Optional Tx Burst.
Transmit IF Frequency Range:	50 to 90 (standard) in 1 Hz Steps.
Receive IF Frequency Range:	50 to 90 (standard) in 1 Hz Steps.
Transmit Output Power: (BNC Programmable 75/50 Ω)	+5 to -35 dBm, programmable in 0.1 dB steps (max. +3 dBm @ 50Ω)
Return Loss	20 dB minimum.
Transmit Output Phase Noise:	Better than IESS-308/309 by 6 dB typical, 4 dB minimum.
Transmit Output Level Stability/Accuracy:	±0.5 dB, 0 ~ 50°C, accurate ±0.5 dB, 50 ~ 90 MHz at 25°C
Transmit Output Spurious/Harmonics:	<-50 dBc / <-50 dBc up to -10 dBm, <-40 dBc @ + 5 dBm out
Receive Carrier Level In: (BNC Programmable 75/50 Ω)	-20 to -60 dBm, scales to -84 at lower data rates. Formula is: minimum = 10log(symbol rate)-120dBm
Return Loss	10 dB minimum.
Maximum Composite Receive Input Power	+15 dBm or +40 dBc whichever is lower power
Receive Demodulator Phase Noise:	Better than IESS-308/309 by 4 dB minimum., 6 dB typical.
Receive Acquisition Range:	Programmable from ± 100 Hz to ± 1.25 MHz
Frequency Reference (Internal) Stability	2 x 10 ⁻⁶ TCXO (Standard),.
External:	External reference input on rear panel for 1, 5, 9, or 10 MHz. Internal TCXO phase locks to external input.
Modulation and Demodulation: PSM-505S: PSM-511S: PSM-523S:	Programmable for BPSK, QPSK, OQPSK, independently Adds 8PSK and 8APSK with Trellis Code Modulation Adds 16QAM and 16APSK
Forward Error Correction: Standard Concatenated Reed-Solomon:	Viterbi standard. k=7. 4 or 16k block Turbo Product Codes optional. n=126, k=112, t=7 or n=219, k=201, t=9 or programmable, depth of 4 or 8
FEC (Viterbi or TPC) Rates Selectable:	1/2, 3/4, 7/8 or disabled. Rate 5/6 in Viterbi only, Rate 2/3 in 8PSK mode.
Data Rates Minimum, all modems at FEC rate: (without IBS mux or R-S option)	1.2 kbps rate 1/2 BPSK, 2.4 kbps, rate 3/4 or 7/8 BPSK 2.4 kbps rate 1/2, 4.8 kbps rate 3/4 or 7/8 QPSK or OQPSK 9.6 kbps all rates 8PSK, 19.2 kbps all rates 16QAM
Data Rates Maximum - PSM-505S: PSM-511S: PSM-523S: (without IBS mux or R-S option) Note – Max rate may be limited by interface	5 Mbps, all modulation modes and FEC rates. 10 Mbps all modulation modes and FEC rates – see Note below 20 Mbps all modulation modes and FEC rates. – see Note below Note: Maximum rate limit of 7.38 Mbps, BPSK, rate 1/2; M520 Maximum rate limit of 14.76 Mbps, QPSK, rate 1/2, 19.68 Mbps 8PSK rate 2/3
IBS Multiplex (Standard Built-In)	IBS framing supporting enhanced buffered RS-232/485 overhead channel, AUPC, remote modem control and variable overhead.
Data Rate Selection: Transmit & Receive:	Programmable in 1bps increments. Accurate to 2 x 10E-12 (relative to reference).
Receive Data FIFO Buffer: Plesiochronous or Doppler Elastic Store	4 bits to 524,280 bits, programmable in 1 bit increments, or in delay time.
Data Interface (All synchronous).	RS-449/422 or V.35 or EIA-530 or RS-232 electronically selectable at DB-37 connector. DB25 and V.35 (M34) adaptors available.
BER Performance: with Viterbi FEC 1/2 rate: 1/2 rate Viterbi +R-S Concatenated FEC: 3/4 rate Viterbi +R-S Concatenated FEC: 1/2 rate Turbo Product Codes FEC: 3/4 rate Turbo Product Codes FEC:	10-7 at 6.0 dB Eb/No, 10-5 at 4.8 dB 10-7 at 3.7 dB, 3.5 dB typical (n=126, k=112) 10-7 at 4.7 dB, 4.5 dB typical 10-7 at 3.0 dB, 2.8 dB typical 10-7 at 3.7 dB, 3.5 dB typical
Fast Receive Lock Performance at FEC rate 1/2, 6.0 dB Eb/No, +/-30kHz acquisition range: (Average)	315 msecond at 9.6 kbps QPSK or 175 msecond at 9.6 kbps BPSK . 71 msecond at 64 kbps.QPSK
Front Panel Control:	LCD display and keypad provide full status and programmability.
Remote Control: Terminal Mode: Packet Mode:	Full screen live display and interactive control of all operating parameters and status. Command packet driven RS-232/485 control and reporting of all parameters and status.
Case Dimensions:	Rack mount @ 1 RU (19"W X 14"D X 1.75"H.)
Input Power Requirements (without BUC):	90 to 264 VAC, 50/60 HZ, Approx. 40 Watts, 60 Watts maximum, fully loaded including LNB power.
Operating Conditions:	0 to 50° C, to 95% humidity, non-condensing.